

1 **Amendment of the Specification (First Amendment p11)**

2 The Specification is amended at page 10/line 21 to page 11/line 21 as follows:

3
4 (Currently Amended) The tube (20) having an inner wall (140) where at least
5 one depression or groove (150) is formed in the inner wall (140) which receives at least
6 one vane (90), of the at least one inner core (70) received into the tube (20), at a vane tip
7 (98) and, as depicted, at least two vane tips (98) are received respectively into at least two
8 grooves (150) formed in the inner wall (140).. The groove (150) comprising vane (90)
9 restraining means securing the at least one inner core (70) in a fixed position within said
10 tube (20). It will be appreciated by those of ordinary skill in the arts that the groove (150)
11 may be a structure extending from the inner wall (140) forming a groove (150) which will
12 receive at least one vane (90). Alternatively it is understood that the groove (150) may be
13 a depression formed into the inner wall (140) capable of receiving the at least one vane
14 (90). As will be appreciated by one of ordinary skill in these arts, vane (90) restraining
15 means may be by a friction fit between the vane tip (98) when received into a groove
16 (150) or by application of an adhesive or a mechanical fixing means between the vane tip
17 (98) and the groove (150). In the preferred embodiment at least two depressions or
18 grooves (150) are formed in the inner wall (140) with each of said grooves (150)
19 receiving at least one vane (90). The at least one vane having a vane surface (92). The at
20 least one vane (90) extending from the central core element (25) along the length of said
21 central core element (25). The surface (92) covered with a biofilm (97). In the preferred
22 embodiment at least eight vanes (90) are spaced equidistant from the adjoining vane (90)
23 and extending from the central core element (25).

24

25

26

27 OFFICIAL RESPONSE Certificate of facsimile
28 filing, Application No. 09/041,685 on
September 7, 2004 by Floyd E. Ivey in response
to Office Action of June 4, 2004

4
Z:\PC\client\Weiss.Cullinan\Portion Revival\Responses\caponisc.112.102.103.Weiss.Response\FINAL.040625.wpd

1 **Amendment of the Specification (Second Amendment p12)**

2 The Specification is amended commencing at page 11/line 22 to page 12/line 17 as
3 follows:

4
5 (Currently amended) The tube (20) having an outer wall (190) having at least
6 one fin (200) extending outwardly therefrom. As depicted the tube (20) has at least four
7 fins (200) extending from said outer wall (190). However, one of ordinary skill in the
8 arts will appreciate that fins of 1...n may be employed in accordance with the space
9 available and surface area desired. The fin (200) is generally elongated having a fin
10 surface (210) and, in the preferred embodiment, extends outwardly from the tube outer
11 wall (190). Where a plurality of tubes (20) are utilized the plurality of tubes (20) contact
12 adjacent tubes (20) at the respective tube outer walls (190) at least one contact point (195)
13 where, in the preferred embodiment, affixing means, ~~including adhesives, mechanical~~
14 ~~fasteners~~ and other methods or devices as are appreciated by those in the affixing arts, are
15 utilized to fix adjacent tubes together and hence to fix the position of the plurality of
16 tubes (20) within the media matrix (1). Tube at least one contact points (195) are, in the
17 preferred embodiment, flattened surfaces extending from the tube top (25) to the tube
18 bottom (30) parallel with the tube axis (37). In an alternative embodiment, tubes (20) in a
19 media matrix (1) may be alternatively or additionally fixed in position by affixing means
20 employed at an intersection of fins (200) of adjoining tubes (20).

21

22

23

24

25

26

27 OFFICIAL RESPONSE Certificate of facsimile
28 filing, Application No. 09/041,685 on
September 7, 2004 by Floyd E. Ivey in response
to Office Action of June 4, 2004.

5
Z:\P\Chad Weiss\Cullinan\Petition Revival\Response\response.112.102.103.Weiss.Response\FINAL.040625.wpd

1 **Amendment of the Specification –(Third Amendment p16)**

2 The Specification is amended from page 16/line 1 through page 17/line 1 as follows:

3

4 The tube (20) having an inner wall (140) where at least one depression or groove
5 (150) is formed in the inner wall (140) which receives at least one vane (90), of the at
6 least one inner core (70) received into the tube (20), at a vane tip (98) and, as depicted, at
7 least two vane tips (98) are received respectively into at least two grooves (150) formed
8 in the inner wall (140).. The groove (150) comprising vane (90) restraining means
9 securing the at least one inner core (70) in a fixed position within said tube (20). It will
10 be appreciated by those of ordinary skill in the arts that the groove (150) may be a
11 structure extending from the inner wall (140) forming a groove (150) which will receive
12 at least one vane (90). Alternatively it is understood that the groove (150) may be a
13 depression formed into the inner wall (140) capable of receiving the at least one vane
14 (90). As will be appreciated by one of ordinary skill in these arts, vane (90) restraining
15 means may be by a friction fit between the vane tip (98) when received into a groove
16 (150) or by application of an adhesive or a mechanical fixing means between the vane tip
17 (98) and the groove (150). In the preferred embodiment at least two depressions or
18 grooves (150) are formed in the inner wall (140) with each of said grooves (150)
19 receiving at least one vane (90). The at lease one vane having a vane surface (92). The at
20 least one vane (90) extending from the central core element (25) along the length of said
21 central core element (25). The surface (92) covered with a biofilm (97). In the preferred
22 embodiment at least eight vanes (90) are spaced equidistant from the adjoining vane (90)
23 and extending from the central core element (25).

24

25

26

27 OFFICIAL RESPONSE Certificate of facsimile
28 filing, Application No. 09/041,685 on
September 7, 2004 by Floyd E. Ivey in response
to Office Action of June 4, 2004.

6
Z:\NP\Client\Weiss, Curtin\Petition Revival\Responses\response.112.102.103.Weiss.Response\FINAL.040625.wpd

1 **Amendment of the Specification - (Fourth amendment p 17)**

2 The Specification is amended at page 17/line 2-page 17/line 21 as follows:

3
4 The tube (20) having an outer wall (190) having at least one fin (200) extending
5 outwardly therefrom. As depicted the tube (20) has at least four fins (200) extending
6 from said outer wall (190). However, one of ordinary skill in the arts will appreciate that
7 fins of 1...n may be employed in accordance with the space available and surface area
8 desired. The fin (200) is generally elongated having a fin surface (210) and, in the
9 preferred embodiment, extends outwardly from the tube outer wall (190). Where a
10 plurality of tubes (20) are utilized the plurality of tubes (20) contact adjacent tubes (20) at
11 the respective tube outer walls (190) at at least one contact point (195) where, in the
12 preferred embodiment, affixing means, ~~including adhesives, mechanical fasteners and~~
13 other methods or devices as are appreciated by those in the affixing arts, are utilized to fix
14 adjacent tubes together and hence to fix the position of the plurality of tubes (20) within
15 the media matrix (1). Tube at least one contact points (195) are, in the preferred
16 embodiment, flattened surfaces extending from the tube top (25) to the tube bottom (30)
17 parallel with the tube axis (37). In an alternative embodiment, tubes (20) in a media
18 matrix (1) may be alternatively or additionally fixed in position by affixing means
19 employed at an intersection of fins (200) of adjoining tubes (20).

20
21
22
23
24
25
26
27 OFFICIAL RESPONSE Certificate of facsimile
28 filing Application No. 09/041,685 on
September 7, 2004 by Floyd E. Ivey in response
to Office Action on June 4, 2004.

Z:\IPClient\Weiss Cullinan\Petition Revival\Response\response.112.102.103.Weiss.Response.FINAL.040625.wpd